





2712 SVC - 4 Ohm

CONNECTIONS	SUGGESTED AMPLIFIERS
	<p>LK 902 - LK 654 LK 2501 Stealth 1 - Stealth 3</p>

Closed Enclosure	
Number of woofers	1 x 2712 SVC
Connection	Single
Nominal Impedance	4 Ohm
Enclosure volume	35 L
Phono-absorbtion	2 Layers - 2 cm thickness
Wood thickness	Medium density 2 cm thickness
Construction	As showed above

Vented Enclosure	
Number of woofers	1 x 2712 SVC
Connection	Single
Nominal Impedance	4 Ohm
Enclosure volume	40 L
Phono-absorbtion	1 Layer - 2 cm thickness
Wood thickness	Medium density 2 cm thickness
Construction	As showed above
Vents	1 pcs - Dual trumpet - Lenght 184 mm - Diam. 69 mm

Bandpass Enclosure	
Number of woofers	1 x 2712 SVC
Connection	Single
Nominal Impedance	4 Ohm
Enclosure volume	Chamber 1: 21 L - Chamber 2: 24 L
Phono-absorbtion	1 Layer - 2 cm thickness each chamber
Wood thickness	Medium density 2 cm thickness
Construction	As showed above
Vents	3 pcs - Dual trumpet - Lenght 184 mm - Diam. 69 mm