





2715 SVC - 4 Ohm

CONNECTIONS	SUGGESTED AMPLIFIERS
	<p>LK 251 Stealth 1 - Stealth 2 Stealth 3</p>

Closed Enclosure	
Number of woofers	1 x 2715 SVC
Connection	Single
Nominal Impedance	4 Ohm
Enclosure volume	50 L
Phono-absorbtion	2 Layers - 2 cm thickness
Wood thickness	Medium density 2 cm thickness
Construction	As showed above

Vented Enclosure	
Number of woofers	1 x 2715 SVC
Connection	Single
Nominal Impedance	4 Ohm
Enclosure volume	60 L
Phono-absorbtion	1 Layer - 2 cm thickness
Wood thickness	Medium density 2 cm thickness
Construction	As showed above
Vents	2 pcs - Dual trumpet - Lenght 182 mm - Diam. 69 mm

Bandpass Enclosure	
Number of woofers	1 x 2715 SVC
Connection	Single
Nominal Impedance	4 Ohm
Enclosure volume	Chamber 1: 43 L - Chamber 2: 43 L
Phono-absorbtion	1 Layer - 2 cm thickness each chamber
Wood thickness	Medium density 2 cm thickness
Construction	As showed above
Vents	4 pcs - Dual trumpet - Lenght 171 mm - Diam. 69 mm